


WELDON BARRIER GATE PLAN

Single Gate Configuration - Curved Support Design

8' wide by 44" tall gate - hung between the posts - using Central Eye Hinges (Product Code #8312).



Distance between latch post and gate	Α
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D

		HARDWARE REQUIRED					
		HARDWARE REQUIRED					
Finish Options Available	Galvanized Finish	Black Powder Coat over Galvanized Finish	Combi	Control Five Ulinas Advantages			
Plan Specified Hinge Set				Central Eye Hinge Advantages Opens both ways 100 degrees.			
Each Set Includes: (All fasteners are included with hardware)	8312-S242	8312-S24P		Incredible amount of adjustment.			
	one 24 inch double strap (8312-542 or 8312-54SP) one adjustable bottom gate fitting (8250-002 or 8250-00P)		Easy operation. Very strong.				
							two 12" adjustable gate pins (880)
	Latch Options			А	В	С	D
Slide Bolt Latch (shown)	5002-L122	5002-L12SP	1"	8'	4.5"	8' - 5.5"	
Quick Catch	4100-3SS	4100-3BSS	1.5"	8'	4.5"	8'-6"	
Throw Over Gate Loop*	4200-032	4200-03SP	5"	8'	4.5"	8' - 9.5"	
		Optional Gate Holdback	A mad	ans of ke	anina a	ata anan	
Heavy Duty Cabin Hook	4270-122	4270-12SP	A means of keeping gate open				
		Lumber Required					
Posts	2 of 8' x 6" x 6" (usually dressed out at 5.5" x 5.5")		Rails, Stiles (uprights) and				
Rails	3 of 8' x 1" x 5.5"			Diagonals made from full 1" thick			
Stiles	2 of 8' x 1" x 5.5"		by 5.5" wide lumber (commonly sold as decking lumber) or 1" rough cut lumber (4/4).				
Diagonals	1 of 8' x 1" x 5.5" (straight support	design) or 2 of 8' x 1" x 5.5" (curved support design)					
Filler Blocks	use off cuts from above						
	Faste	eners Required for Gate Construction					

FP-WeldonBarr. - Fastener Pack for Weldon Barrier Gate Build (Includes 40 of 1.75" wood screws, 2 of 3/8" dowel rod and 9 of 3.5" HDG carriage bolts, nuts and washers) *Using the Throw Over Gate Loop (4200-032 or 4200-03SP) will require you to build a receiver for the latch onto the latch post.

