

SINGLE CAPE COD RAIL GATE (4 FOOT WIDE 46" HIGH GATE WITH 74" STILE) REAR EYE HINGES (Product Codes #8324) GATE HUNG BETWEEN POSTS

Distance between latch post and gate	А
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D

		Hardware Required					
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Rear Eye Hinge Advantages				
Hinge Set	8324-S122	8324-S12P	Opens 180 degrees				
fasteners included		Set Includes	Incredible amount of adjustment				
with hardware	two 12 inch double strap (8324-122 or	8324-12SP)	Easy operation & Very Strong				
	two mounting plate with 8" adjustable threaded pins(8256-342 or 8256-34P)		Minimal space between gate & post				
Latch Options			Dimensions (feet and inches)				
Lateri Options		Α	В	С	D		
Irish Gate Latch (shown above)	8328-002	8328-00SP	1"	4'	1"	4' 2"	
Spring Latch	8327-002	8327-00P	4"	4'	1"	4' 5"	
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	4'	1"	4' 2"	
	•	Lumber Required		-5	-	-	
Posts	2 of 10' x 6" x6" (usually dressed out a	at 5.5" x 5.5")					
Rails, Stiles (uprig	hts) and Diagonals made from full 1" thi	ck by 5.5" wide lumber (commonly stocked decking ma	iterial or ro	ugh cut l	umber)		
Rails	2 of 8' x 1" x 5.5"						
Stiles	3 of 8' x 1" x 5.5"						
Diagonals	2 of 8' x 1" x 5.5"						
Filler Blocks	1 of 12' x 1" x 5.5" (Parts E,F,G and H on Plan Layout)						
		Fasteners Required					
Approximately 50 of 1.75" x #8 w	ood screws (stainless preferred)						
14 of 3.5" x 3/8" carriage bolts (h	ot dipped galvanized or stainless steel),	nuts, and washers					
Mounting Plate Fasteners - 10 of	3/8" carriage bolts that are1" longer tha	n thickness of gate post (preferred) or 10 of 3/8" lag bo	lts (minim	um of 4"	long)		
	Use a 24" Cane Bolt (5000-242 or 5	000-24SP) if you require a means of keeping the gate of	open				

