

SINGLE CAPE COD RAIL GATE (6 FOOT WIDE 46" HIGH GATE WITH 74" STILE) REAR EYE HINGES (Product Codes #8324) GATE HUNG BETWEEN POSTS

Distance between latch post and gate	Α
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D

		Hardware Required						
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Rea	Rear Eye Hinge Advantages				
Hinge Set	8324-S182	8324-S18P	Opens 180 degrees					
fasteners included		Set Includes	Incredible amount of adjustment					
with hardware	two 18 inch double strap (8324-182 or	8324-18SP)	Eas	Easy operation & Very Strong				
	two mounting plate with 8" adjustable threaded pins (8256-342 or 8256-34P)		Minimal space between gate & post					
Latch Options		Dimensions (feet and inches)						
		Α	В	С	D			
Irish Gate Latch (shown above)	8328-002	8328-00SP	1"	6'	1"	6' 2"		
Spring Latch	8327-002	8327-00P	4"	6'	1"	6' 5"		
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	6'	1"	6' 2"		
	•	Lumber Required	-					
Posts	2 of 10' x 6" x6" (usually dressed out a	at 5.5" x 5.5")						
Rails, Stiles (uprig	ghts) and Diagonals made from full 1" th	ick by 5.5" wide lumber (commonly stocked decking ma	terial or ro	ugh cut	lumber)			
Rails	2 of 12' x 1" x 5.5"							
Stiles	3 of 8' x 1" x 5.5"							
Diagonals	2 of 8' x 1" x 5.5"							
Filler Blocks	2 of 8' x 1" x 5.5" (Parts E,F,G and H on Plan Layout)							
		Fasteners Required						
Approximately 50 of 1.75" x #8 w	ood screws (stainless preferred)							
14 of 3.5" x 3/8" carriage bolts (h	ot dipped galvanized or stainless steel),	, nuts, and washers						
Mounting Plate Fasteners - 10 of	3/8" carriage bolts that are1" longer that	an thickness of gate post (preferred) or 10 of 3/8" lag bo	lts (minimu	ım of 4" l	long)			
	Use a 24" Cane Bolt (5000-242 or 5	5000-24SP) if you require a means of keeping the gate of	pen					

Hoover Fence Company

