

SINGLE CAPE COD RAIL GATE (8 FOOT WIDE 46" HIGH GATE) CENTRAL EYE HINGES (Product Codes #8312) GATE HUNG BETWEEN POSTS

Distance between latch post and gate	А
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D

		Hardware Required					
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Central Eye Hinge Advantages				
Hinge Set	8312-S242	8312-S24P					
fasteners included	Set Includes Opens both way				vays 100	ays 100 degrees	
with hardware	one 24 inch double strap (8312-542 or	· 8312-54SP)	Incredible amount of adjustment				
	one adjustable bottom gate fitting (8250-002 or 8250-00P)		Easy operation				
	two 12" adjustable gate pin (8800-122	or 8800-12P)	Very strong				
Latch Options			Dimensions (feet and inches)				
			Α	В	С	D	
Irish Gate Latch (shown above)	8328-002	8328-00SP	1"	8'	4.5"	8' 5.5"	
Spring Latch	8327-002	8327-00P	4"	8'	4.5"	8' 9.5"	
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	8'	4.5"	8' 5.5"	
		Lumber Required					
Posts	2 of 10' x 6" x6" (usually dressed out a	at 5.5" x 5.5")					
Rails, Stiles (uprigh	nts) and Diagonals made from full 1" thic	ck by 5.5" wide lumber (commonly stocked decking mate	erial or rou	gh cut lu	ımber)		
Rails	4 of 8' x 1" x 5.5"						
Stiles	3 of 8' x 1" x 5.5"						
Diagonals	2 of 10' x 1" x 5.5"						
Filler Blocks	2 of 10' x 1" x 5.5" (Parts E,F, and G o	n Plan Layout)					
		Fasteners Required					
Approximately 50 of 1.75" x #8 w	ood screws (stainless preferred)						
16 of 3.5" x 3/8" carriage bolts (h	ot dipped galvanized or stainless steel),	nuts, and washers					
	Use a 24" Cane Bolt (5000-242 or 50	000-24SP) if you require a means of keeping the gate op	en				

Hoover Fence Company

Download includes this materials list, component cutting and layout sheet, tips on installing gate posts, and detailed instructions. For a complete listing of our free gate plans and gate layouts visit hooverfence.com.

