

SINGLE CAPE COD RAIL GATE (8 FOOT WIDE 46" HIGH GATE WITH 74" STILE) REAR EYE HINGES (Product Codes #8324) GATE HUNG BETWEEN POSTS

Distance between latch post and gate	А
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D

		Hardware Required					
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Rear Eye Hinge Advantages Opens 180 degrees				
Hinge Set	8324-S242	8324-S24P					
fasteners included	Set Includes			Incredible amount of adjustment			
with hardware	two 24 inch double strap (8324-242 or 8324-24SP)		Easy operation & Very Strong				
	two mounting plate with 8" adjustable threaded pins (8256-342 or 8256-34P)		Minimal space between gate & post				
			Dimensions (feet and inches)				
Latch Options		Α	В	С	D		
Irish Gate Latch (shown above)	8328-002	8328-00SP	1"	8'	1"	8' 2"	
Spring Latch	8327-002	8327-00P	4"	8'	1"	8' 5"	
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	8'	1"	8' 2"	
		Lumber Required	-				
Posts	2 of 10' x 6" x6" (usually dressed out a	at 5.5" x 5.5")					
Rails, Stiles (uprig	hts) and Diagonals made from full 1" th	ick by 5.5" wide lumber (commonly stocked decking ma	terial or ro	ough cut	lumber)		
Rails	4 of 8' x 1" x 5.5"						
Stiles	3 of 8' x 1" x 5.5"						
Diagonals	2 of 10' x 1" x 5.5"						
Filler Blocks	2 of 12' x 1" x 5.5" (Parts E,F,G and H	on Plan Layout)					
	·	Fasteners Required					
Approximately 50 of 1.75" x #8 w	ood screws (stainless preferred)						
16 of 3.5" x 3/8" carriage bolts (h	ot dipped galvanized or stainless steel),	nuts, and washers					
Mounting Plate Fasteners - 10 of	3/8" carriage bolts that are1" longer tha	an thickness of gate post (preferred) or 10 of 3/8" lag bo	lts (minim	um of 4"	long)		
		6000-24SP) if you require a means of keeping the gate of			<u> </u>		

Hoover Fence Company

