

DOUBLE DUMPSTER GATES (TWO 7 FOOT WIDE 96" HIGH GATES) REAR EYE HINGES (Product Codes #8324) GATE HUNG BETWEEN POSTS

Distance between gate and hinge post	Α
Width of Left Gate	В
Distance between gates	С
Width of Right Gate	D
Distance between gate and hinge post	Е
Total distance between posts	F

		Hardware Required								
	Galvanized Finish	Black Powder Coat over Galvanized Finish		Rear Eye Hinge Advantages						
Hinge Sets	2 of 8324-S242	2 of 8324-S24P		Opens 180 degrees						
fasteners included	Two Sets Includes				Incredible amount of adjustment					
with hardware	four 24 inch double strap (8324-242 or 8324-24SP)				Easy operation & Very Strong					
	four mounting plate with 8" adjustable threaded pins(8256-342 or 8256-34P)			Minimal distance between						
Cane Bolt (Vertical)	2 of 5000-362	2 of 5000-36SP		gate and post						
Central Latch Options		Dimensions (feet and inches)								
		.10115	Α	В	С	D	Е	F		
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	7'	1"	7'	1"	14' 3"		
		Lumber Required								
Posts	2 of 12' x 6" x6" (usually dressed out	at 5.5" x 5.5")								
Rails, Stiles (u	prights) and Diagonals made from full 1" the	nick by 5.5" wide lumber (commonly stocked decking ma	iterial o	r rougl	n cut lu	umber	.)			
Rails	6 of 14' x 1" x 5.5"									
Stiles	4 of 8' x 1" x 5.5"									
Diagonals	2 of 14' x 1" x 5.5"									
Vertical Boards for Front	32 of 8' x 1" x 5.5"									
		Fasteners Required								
Approximately 100 of 1.75" x	#8 wood screws (stainless preferred)									
28 of 3.5" x 3/8" carriage bolts	s (hot dipped galvanized or stainless steel)	, nuts, and washers								
Mounting Plate Fasteners - 20	of 3/8" carriage bolts that are 1" longer th	nan thickness of gate post (preferred) or 20 of 3/8" lag bo	olts (mir	nimum	of 4" I	ong)				

