
SINGLE MAINE BOARD RAIL GATE (10 FOOT WIDE 46" HIGH GATE) REAR EYE HINGES (Product Codes #8324) GATE HUNG BETWEEN POSTS



Distance between latch post and gate	Α
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D

		Hardware Required						
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Rear Eye Hinge Advantages					
Hinge Set	8324-S242	8324-S24P	Opens 180 degrees					
fasteners included	Set Includes			Incredible amount of adjustment				
with hardware	two 24 inch double strap (8324-242 or 8324-24SP)		Easy operation & Very Strong					
	two mounting plate with 8" adjustable threaded pins (8256-342 or 8256-34P)			Minimal space between gate & post				
Latch Options					Dimensions (feet and inches)			
	Laterr Options		Α	В	С	D		
Irish Gate Latch (shown above)	8328-002	8328-00SP	1"	10'	1"	10' 2"		
Spring Latch	8327-002	8327-00P	4"	10'	1"	10' 5"		
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	10'	1"	10' 2"		
		Lumber Required						
Posts 2 of 8' x 6" x6" (usually dressed out at 5.5" x 5.5")								
Rails, Stiles (uprig	ghts) and Diagonals made from full 1" th	ick by 5.5" wide lumber (commonly stocked decking ma	aterial or ro	ugh cut	lumber)			
ails 6 of 10' x 1" x 5.5"								
Stiles 2 of 8' x 1" x 5.5"								
Diagonals 2 of 10' x 1" x 5.5"								
Filler blocks for bottom hinge	1 of 8' x 1" x 5.5"							
		Fasteners Required						
Approximately 50 of 1.75" x #8 w	vood screws (stainless preferred)							
12 of 3.5" x 3/8" carriage bolts (h	not dipped galvanized or stainless steel),	nuts, and washers						
Mounting Plate Fasteners - 10 of	f 3/8" carriage bolts that are1" longer tha	an thickness of gate post (preferred) or 10 of 3/8" lag bo	lts (minimu	um of 4"	long)			
	Use a 24" Cane Bolt (5000-242 or 5	5000-24SP) if you require a means of keeping the gate	open					

