
DOUBLE MAINE BOARD RAIL GATE (TWO 4 FOOT WIDE 46" HIGH GATES) CENTRAL EYE HINGES (Product Codes #8312) GATE HUNG BETWEEN POSTS



Distance between gate and hinge post	А
Width of Left Gate	В
Distance between gates	С
Width of Right Gate	D
Distance between gate and hinge post	E
Total distance between posts	F

	<u>-</u>	Hardware Required							
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Ce	Central Eye Hinge Advantages					
Hinge Sets	2 of 8312-S122	2 of 8312-S12P			_, -	9-		3	
fasteners included	Two Sets Includes			Opens both ways 100 degrees					
with hardware	two 12 inch double strap (8312-422 or		Incredible amount of adjustment						
	two adjustable bottom gate fitting (8250-002 or 8250-00P)			Easy operation					
four 12" adjustable gate pin (8800-122 or 8800-12P)				Very strong					
Cane Bolt (Vertical)	1 or 2 of 5000-242*	1 or 2 of 5000-24SP*							
Central Latch Options				Dimensions (feet and inches)					
Certifal Lateri Options		Olis	Α	В	С	D	Е	F	
Throw Over Gate Loop	4200-032	4200-03SP	4.5"	4'	1"	4'	4.5"	8' 10"	
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	4.5"	4'	1"	4'	4.5"	8' 10"	
		Lumber Required	-						
Posts	2 of 8' x 6" x6" (usually dressed out at								
		ick by 5.5" wide lumber (commonly stocked decking r	naterial or	rougl	h cut l	umbe	r)		
Rails	6 of 8' x 1" x 5.5"								
Stiles	4 of 8' x 1" x 5.5"								
Diagonals	2 of 10' x 1" x 5.5"								
		Fasteners Required							
	#8 wood screws (stainless preferred)								
	s (hot dipped galvanized or stainless steel),								
*One 24" Cane Bo	olt (5000-242 or 5000-24SP) is required for	central stability. Two are needed if you require a me	eans of ke	eping	the ga	ates o	pen.		

Hoover Fence Company

