

SINGLE MAINE BOARD RAIL GATE (5 FOOT WIDE 46" HIGH GATE) REAR EYE HINGES (Product Codes #8324) GATE HUNG BETWEEN POSTS



Distance between latch post and gate	Α
Width of Gate	В
Distance between gate and hinge post	С
Total distance between posts	D


		Hardware Required				
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Rea	Rear Eye Hinge Advantages		
Hinge Set	8324-S182	8324-S18P		Opens 180 degrees		
fasteners included		Set Includes	Incre	Incredible amount of adjustment		
with hardware	two 18 inch double strap (8324-182 or	8324-18SP)	Eas	Easy operation & Very Strong		
	two mounting plate with 8" adjustable threaded pins (8256-342 or 8256-34P)		Minimal space between gate & post			
Latch Options		Dimensions (feet and inches)				
	Laten Options		Α	В	С	D
Irish Gate Latch (shown above)	8328-002	8328-00SP	1"	5'	1"	5' 2"
Spring Latch	8327-002	8327-00P	4"	5'	1"	5' 5"
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	5'	1"	5' 2"
		Lumber Required				
Posts	2 of 8' x 6" x6" (usually dressed out at	t 5.5" x 5.5")				
Rails, Stiles (uprig	hts) and Diagonals made from full 1" thi	ick by 5.5" wide lumber (commonly stocked decking ma	terial or ro	ugh cut l	lumber)	
Rails	3 of 10' x 1" x 5.5"					
Stiles	2 of 8' x 1" x 5.5"					
Diagonals	1 of 12' x 1" x 5.5"					
Filler blocks for bottom hinge	1 of 8' x 1" x 5.5"					
		Fasteners Required				
Approximately 50 of 1.75" x #8 w	rood screws (stainless preferred)					
12 of 3.5" x 3/8" carriage bolts (h	ot dipped galvanized or stainless steel),	, nuts, and washers				
Mounting Plate Fasteners - 10 of	3/8" carriage bolts that are1" longer that	an thickness of gate post (preferred) or 10 of 3/8" lag bo	olts (minimu	ım of 4"	long)	
	Use a 24" Cane Bolt (5000-242 or 5	5000-24SP) if you require a means of keeping the gate of	open			




COMPONENTS (FULL 1" THICK x 5-1/2" WIDE)











Hoover Fence Company 5' Maine Board Gate



FLAT FRONTAL VIEW



THREE LAYERS

