
DOUBLE MAINE BOARD RAIL GATE (TWO 5 FOOT WIDE 46" HIGH GATES) CENTRAL EYE HINGES (Product Codes #8312) GATE HUNG BETWEEN POSTS



| Distance between gate and hinge post | А |
|--------------------------------------|---|
| Width of Left Gate | В |
| Distance between gates | С |
| Width of Right Gate | D |
| Distance between gate and hinge post | E |
| Total distance between posts | F |

| | | Hardware Required | | | | | | | |
|-----------------------|---|--|------------|------------------------------|----------|--------|------|---------|--|
| | Galvanized Finish | Black Powder Coat over Galvanized Finish | Ce | Central Eye Hinge Advantages | | | | ntages | |
| Hinge Sets | 2 of 8312-S182 | 2 of 8312-S18P | | | | | | | |
| fasteners included | Two Sets Includes | | | Opens both ways 100 degrees | | | | | |
| with hardware | two 18 inch double strap (8312-482 o | Incredible amount of adjustment | | | | | | | |
| | two adjustable bottom gate fitting (8250-002 or 8250-00P) | | | Easy operation | | | | | |
| | four 12" adjustable gate pin (8800-122 or 8800-12P) | | | Very strong | | | | | |
| Cane Bolt (Vertical) | 1 or 2 of 5000-242* | 1 or 2 of 5000-24SP* | | | | | | | |
| Central Latch Options | | | [| Dimensions (feet and inches) | | | | | |
| | | Α | В | С | D | E | F | | |
| Throw Over Gate Loop | 4200-032 | 4200-03SP | 4.5" | 5' | 1" | 5' | 4.5" | 10' 10" | |
| Cane Bolt and Keep | 5000-122 plus 5000-002 | 5000-12SP plus 5000-00SP | 4.5" | 5' | 1" | 5' | 4.5" | 10' 10" | |
| | | Lumber Required | | | | | | | |
| Posts | 2 of 8' x 6" x6" (usually dressed out a | , | | | | | | | |
| | | hick by 5.5" wide lumber (commonly stocked decking ma | aterial or | roug | n cut li | umbe | r) | | |
| Rails | 6 of 10' x 1" x 5.5" | | | | | | | | |
| Stiles | 4 of 8' x 1" x 5.5" | | | | | | | | |
| Diagonals | 2 of 12' x 1" x 5.5" | | | | | | | | |
| | | Fasteners Required | | | | | | | |
| · · · | #8 wood screws (stainless preferred) | | | | | | | | |
| | (hot dipped galvanized or stainless steel) | | | | | | | | |
| *One 24" Cane Bo | It (5000-242 or 5000-24SP) is required fo | r central stability. Two are needed if you require a mea | ins of ke | eping | the ga | ates o | pen. | | |

Hoover Fence Company

Download includes this materials list, component cutting and layout sheet, tips on installing gate posts, and detailed instructions.

For a complete listing of our free gate plans and gate layouts visit hooverfence.com.

