
DOUBLE MAINE BOARD RAIL GATE (TWO 6 FOOT WIDE 46" HIGH GATES) CENTRAL EYE HINGES (Product Codes #8312) GATE HUNG BETWEEN POSTS




Distance between gate and hinge post	А
Width of Left Gate	В
Distance between gates	С
Width of Right Gate	D
Distance between gate and hinge post	E
Total distance between posts	F

		Hardware Required							
	Galvanized Finish	Black Powder Coat over Galvanized Finish	C	Central Eye Hinge Advantages					
Hinge Sets	2 of 8312-S182	2 of 8312-S18P							
fasteners included	Two Sets Includes			Opens both ways 100 degrees					
with hardware	two 18 inch double strap (8312-482 or	8312-48SP)	Incredible amount of adjustment						
	two adjustable bottom gate fitting (8250-002 or 8250-00P) four 12" adjustable gate pin (8800-122 or 8800-12P)			Easy operation					
				Very strong					
Cane Bolt (Vertical)	1 or 2 of 5000-242*	1 or 2 of 5000-24SP*							
Central Latch Options				Dimensions (feet and inches)					
		A	В	С	D	E	F		
Throw Over Gate Loop	4200-032	4200-03SP	4.5"	6'	1"	6'	4.5"	12' 10"	
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	4.5"	6'	1"	6'	4.5"	12' 10"	
		Lumber Required							
Posts	2 of 8' x 6" x6" (usually dressed out at								
		ick by 5.5" wide lumber (commonly stocked decking ma	aterial or	rougl	n cut lu	umbe	-)		
Rails	6 of 12' x 1" x 5.5"								
Stiles	4 of 8' x 1" x 5.5"								
Diagonals	2 of 14' x 1" x 5.5"								
		Fasteners Required							
	3 wood screws (stainless preferred)								
	hot dipped galvanized or stainless steel),								
*One 24" Cane Bolt	: (5000-242 or 5000-24SP) is required for	central stability. Two are needed if you require a mea	ans of ke	eping	the ga	ates o	pen.		

Hoover Fence Company

Download includes this materials list, component cutting and layout sheet, tips on installing gate posts, and detailed instructions.

For a complete listing of our free gate plans and gate layouts visit hooverfence.com.



THREE LAYERS D F В

