
DOUBLE MAINE BOARD RAIL GATE (TWO 6 FOOT WIDE 46" HIGH GATES) REAR EYE HINGES (Product Codes #8324) GATE HUNG BETWEEN POSTS



		Hardware Required							
	Galvanized Finish	Black Powder Coat over Galvanized Finish	F	Rear Eye Hinge Advantages					
Hinge Sets	2 of 8324-S182	2 of 8324-S18P		Opens 180 degrees					
fasteners included	Two Sets Includes			Incredible amount of adjustment					
with hardware	four 18 inch double strap (8324-182 or 8324-18SP)			Easy operation & Very Strong					
	four mounting plate with 8" adjustable threaded pins(8256-342 or 8256-34P)		Minimal distance between						
Cane Bolt (Vertical)	1 or 2 of 5000-242*	1 or 2 of 5000-24SP*		gate and post					
Central Latch Options			Dimensions (feet and inches)						
	Central Later Opti	10115	А	В	С	D	Е	F	
Throw Over Gate Loop	4200-032	4200-03SP	1"	6'	1"	6'	1"	12' 3"	
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	1"	6'	1"	6'	1"	12' 3"	
		Lumber Required							
Posts	2 of 8' x 6" x6" (usually dressed out at	t 5.5" x 5.5")							
Rails, Stiles (upr	ights) and Diagonals made from full 1" th	nick by 5.5" wide lumber (commonly stocked decking m	aterial or	rougl	n cut lu	umber	.)		
Rails	6 of 12' x 1" x 5.5"								
Stiles	4 of 8' x 1" x 5.5"								
Diagonals	2 of 14' x 1" x 5.5"								
Filler blocks for bottom hinge	1 of 8' x 1" x 5.5"								
	-	Fasteners Required							
Approximately 100 of 1.75" x #8	3 wood screws (stainless preferred)								
24 of 3.5" x 3/8" carriage bolts (hot dipped galvanized or stainless steel).	, nuts, and washers							
Mounting Plate Fasteners - 20 c	of 3/8" carriage bolts that are 1" longer th	an thickness of gate post (preferred) or 20 of 3/8" lag b	olts (min	imum	of 4" I	ong)			
*One 24" Cane Bolt	(5000-242 or 5000-24SP) is required for	r central stability. Two are needed if you require a mea	ans of ke	eping	the ga	ates o	pen.		
		Haavan Fanaa Campany							

