
DOUBLE MAINE BOARD RAIL GATE (TWO 8 FOOT WIDE 46" HIGH GATES) CENTRAL EYE HINGES (Product Codes #8312) GATE HUNG BETWEEN POSTS



Distance between gate and hinge post	Α
Width of Left Gate	В
Distance between gates	С
Width of Right Gate	D
Distance between gate and hinge post	E
Total distance between posts	F

		Hardware Required						
	Galvanized Finish	Black Powder Coat over Galvanized Finish	Ce	Central Eye Hinge Advantages				
Hinge Sets	2 of 8312-S242	2 of 8312-S24P						
fasteners included	Two Sets Includes Opens both ways 100 de						grees	
with hardware	two 24 inch double strap (8312-542 or	8312-54SP)	In	Incredible amount of adjustment				
	two adjustable bottom gate fitting (8250-002 or 8250-00P)			Easy operation				
	four 12" adjustable gate pin (8800-122 or 8800-12P)			Very strong				
Cane Bolt (Vertical)	1 or 2 of 5000-242*	1 or 2 of 5000-24SP*						
Central Latch Options			Dimensions (feet and inches)					
		Α	В	С	D	E	F	
Throw Over Gate Loop	4200-032	4200-03SP	4.5"	8'	1"	8'	4.5"	16' 10"
Cane Bolt and Keep	5000-122 plus 5000-002	5000-12SP plus 5000-00SP	4.5"	8'	1"	8'	4.5"	16' 10"
		Lumber Required						
Posts 2 of 8' x 6" x6" (usually dressed out at 5.5" x 5.5")								
	<u></u>	iick by 5.5" wide lumber (commonly stocked decking m	aterial or	rough	n cut lu	umbei	r)	
Rails	12 of 8' x 1" x 5.5"							
Stiles	4 of 8' x 1" x 5.5"							
Diagonals	4 of 8' x 1" x 5.5"							
		Fasteners Required						
	8 wood screws (stainless preferred)							
	(hot dipped galvanized or stainless steel),							
*One 24" Cane Bol	t (5000-242 or 5000-24SP) is required for	central stability. Two are needed if you require a mea	ans of ke	eping	the ga	ates o	pen.	

Hoover Fence Company

