



# Swinger 300

## Pedestrian Gate Closer

### Part 1 GENERAL

#### 1.1 SECTION INCLUDES

- A. Swinger 300 – Pedestrian Gate Closer
- B. Features:
  - 1. Tough, dependable and Vandal resistant
  - 2. 2" x 4" x 12" (16 gauge) galvanized steel housing
  - 3. Gate closer manufactured for pedestrian gates
  - 4. Two separate Closing and Latching valves adjustable after installation without Removing the closer
  - 5. Non-handed (right or left swing)
  - 6. Opens to a full 105°
  - 7. Fully adjustable top arm for proper gate alignment
  - 8. Adjustable zinc plated Bottom Hinge with sealed ball bearings rated for 350 lbs.
  - 9. Designed to close gate into latch position without slamming
  - 10. Smooth operation
  - 11. Adjustable spring power to accommodate various gate sizes
  - 12. Factory tested to over 1,000,000 cycles

#### 1.2 SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Preparation instructions and recommendations
  - 2. Storage and handling requirements and recommendations
  - 3. Installation methods
- B. Shop Drawings: Manufacturer's approved drawings detail the application
- C. Section Samples: Samples are available depicting the finish types
- D. Verification Samples: For the finish product specified, two full size samples representing actual product, color and size

#### 1.4 QUALITY ASSURANCE

Manufacturer Qualifications: The Swinger 300 will be provided by a single manufacturer with over 30 years of experience in door closers

## **1.5 DELIVERY, STORAGE AND HANDLING**

- A. Store products in manufacturer's unopened packing until ready for installation
- B. No harsh chemicals are used during this process, so no special handling or disposal is required

## **1.6 PROJECT CONDITIONS**

Maintain environmental conditions (temperature, humidity and ventilation) within limits recommended by the manufacturer for optimum results. Do not install this product if environmental conditions are outside the manufacturer's limits.

## **1.7 WARRANTY**

After project completion, the owner or owner's representative will receive a copy of the Manufacturer's Limited Warranty against manufacturing defects.

## **Part 2 PRODUCTS**

### **2.1 MANUFACTURER**

International Door Closers Inc., (Manufacturer's Rep)

1140 North Kraemer Pl, Anaheim, CA 92806 - (800) 544-4422  
1920 Air Lane Dr, Nashville, TN 37120 - (800) 225-6737

## **Part 3 EXECUTIONS**

### **3.1 EXAMINATION**

- A. Do not begin installation until substrates have been properly prepared
- B. If the substrate is the responsibility of another installer, notify the Architect of any unsatisfactory preparation before proceeding

### **3.2 PREPARATION**

- A. Clean surfaces thoroughly prior to installation
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best results for the substrate under the project conditions

### **3.3 INSTALLATION**

- A. Install in accordance with manufacturer's instructions

### **3.4 PROTECTION**

- A. Protect installed products until completion of project
- B. Repair or replace all damaged products before substantial completion

**END OF SECTION**