SUPERLOCK LATCH DEADLOCK



- G Easy to fit Slim 2-3/4" wide stainless steel lock case along with adjustable and removable latchbolt ensure easy fitting to gates.
- G Latchbolt is adjustable in length for precise fitting on site. Easy to rotate for left and right handed gates.
- G Supplied with handles two styles available.
- G Supplied with bolt support plate and gate post strike plate.



PRODUCT DETAILS

Product code:	Description:
BLD1030 BLD4060	To fit 3/8" up to 1-1/4" box section To fit 1-1/2" to 2-1/2" box section
Style of handle:	Description:
T S	Traditional handle set Black lever handle set
Bolts:	Adjustable, latchbolt moves $5/8$ " and deadlocks to $1-1/8$ "

For use on both LH/RH gates.



INSTALLATION

- 1. Drill 2 x 3/8" holes at 5-1/2" centres for fixing bolts provided.
- Drill a second 3/4" clearance hole for the latchbolt at 2-3/8" centres up from the bottom fixing hole.
- 4. Hold the lock against the back of the box section and screw the latchbolt through the bottom 3/4" hole.
- Lock the latchbolt and deadbolt with the hex key supplied by inserting the hex key into the end of the latchbolt and the deadbolt.
- Fix lock in place using the stainless steel bolt support plate and the countersunk screws provided. Ensure the latchbolt and deadbolt move freely.
- 7. Fix stike plate by either welding or screw fixing onto the gate post
- MAINTENANCE Every 6 months, lubricate the latchbolt and deadbolt with light oil. Annually, dismantle the lock and spray mechanism with light oil.



© Copyright Gatemaster 2019 +44 (0)1243 552066