

HELLO, MY NAME IS

WT-40

HIGH-STRENGTH FENCE FRAMEWORK

**FORGET THE OTHER GUY.  
HE LEFT THE INDUSTRY.**

**FOUR LAYERS  
OF PROTECTION**

Zinc-rich coating (exceeds  
ASTM standards)

Continuous in-line  
galvanized coating

Intermediate  
pretreatment

Clear polymer  
coating

You probably already have Wheatland Tube's WT-40 in your warehouse — you've just been calling it by the wrong name. But it's been around for years! And now that the other manufacturer has left the fence industry, it's time to call Wheatland's product by the right name. WT-40. The *only* name in high-strength fence framework.

**For more information, visit [wheatland.com/WT-40](http://wheatland.com/WT-40)  
or call 800.257.8182.**



**Wheatland** Tube  
A DIVISION OF ZEKELMAN INDUSTRIES





**Wheatland fence framework is backed by more than 130 years of quality and experience.**

- Wheatland WT-40 framework meets or exceeds ASTM F1043, Standard Specification for Strength and Protective Coatings on Steel Industrial Chain Link Fence Framework.
- Wheatland pipe is Made in America and 100% recyclable.
- Wheatland is the only manufacturer that produces all products to meet ASTM F1083 and ASTM F1043, Groups 1A, 1C and IV standards.

**WT-40 DIMENSIONS AND STRENGTH CHARACTERISTICS**

FENCE INDUSTRY	DECIMAL OD EQUIVALENT		PIPE WALL THICKNESS		WEIGHT		SECTION MODULUS		x	MIN. YIELD STRENGTH		=	MAX. BENDING MOMENT	CALCULATED LOAD (LBS.)		
	in.	(mm)	in.	(mm)	lb./ft.	(kg/m)	in. <sup>3</sup>	(mm <sup>2</sup> )		psi	(MPa)			lb./in.	10' Free Supported	Cantilever
OD														4'	6'	
1½"	1.660	42.16	0.111	2.82	1.84	2.74	0.1962	4.98	x	50000	345	=	9810	327	204	136
1¾"	1.900	48.26	0.120	3.05	2.28	3.39	0.2810	7.14	x	50000	345	=	14050	468	293	195
2½"	2.375	60.33	0.130	3.30	3.12	4.64	0.4881	12.40	x	50000	345	=	24405	814	508	339
2¾"	2.875	73.03	0.160	4.06	4.64	6.91	0.8778	22.30	x	50000	345	=	43890	1463	914	610
3½"	3.500	88.90	0.160	4.06	5.71	8.50	1.3408	34.06	x	50000	345	=	67042	2235	1397	931
4"	4.000	101.60	0.160	4.06	6.56	9.76	1.7820	45.26	x	50000	345	=	89098	2970	1856	1237

6½" and 8½" full-weight Schedule 40 per ASTM F1083 is available for terminal post applications.  
 Specifications, illustrated material and descriptions are accurate as known at time of publication and are subject to change without notice.

WFE-021819

 4435 S. Western Boulevard  
 Chicago, IL 60609  
 P 800.257.8182  
 F 724.346.7260

2001 East Dominguez Street  
 Long Beach, CA 90810  
 P 800.257.8182  
 F 724.346.7260

info@wheatland.com  
 wheatland.com  
 Follow us on Twitter:  
 @WheatlandTube

