

# CELLOPENER-365



## GSM ACCESS CONTROL

This GSM access control system allows up to 2000 registered users to operate any garage door / gate using their phone with no cost for the call to the user. This simple to use access control system uses a GSM SIM card that must be activated upon installation. Simply dial the associated phone number for the SIM Card from any phone or mobile-phone and the gate will open without any cost of a call to you. The CelloPener-365 also allows for an input contact to be used to trigger a SMS text message to a property manager letting them know that someone is at the gate or door.

In addition, the unit offers Weekly Timer and 365 Day Timer capability to offer maximum security and allow a property manager to prevent a gate or overhead door from opening on certain days and times such as national holidays or special events. The current date and time is automatically set via the GSM network so there is never a reason to ever make adjustments for daylight savings time.

All programming of the CelloPener-365 occurs using simple SMS text commands. This feature allows programming to be done remotely from anywhere in the world making life easy for maintenance, security and HR staffs that need to enable or disable an individual person's access to a site.



# CELLOPENER-365

scan here for more  
information



### EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

Phone: 800 426 9912

Fax: 216 518 9884

Sales Inquiries: [salessupport@emxinc.com](mailto:salessupport@emxinc.com)

Technical Support: [technical@emxinc.com](mailto:technical@emxinc.com)

[www.emxinc.com](http://www.emxinc.com)



## EMX CELLOPENER-365

- 12-18 VAC/DC
- Up to 2000 Programmable Users
- Cell Phone SMS Activation
- Weekly & 365 Day timer
- Remote Programming From Anywhere in the World



CELLOPENER-365

## TECHNICAL DATA

<b>Power</b>	12V – 18V AC or DC
<b>Cellular Networks</b>	3G, 4G
<b>Standby Current-LEDs enabled</b>	23mA @ 12 VDC / 16mA @ 18 VDC
<b>Standby Current-LEDs disabled</b>	20mA @ 12 VDC / 14mA @ 18 VDC
<b>Max Authorized Users</b>	1600 Normal Users and 400 Special Users
<b>Relay Contact Rating</b>	5A @ 24V
<b>Operating Temperature</b>	Min -40°C / Max 65°C
<b>Antenna Cable Length</b>	1 m (39.4 inches)
<b>Lead Cable Length</b>	0.5 m (19.7 inches)

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of sale to our customer. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship. Rev 3 12/06/2022

