





# Quick Catch Stainless Steel Field Gate Latch

Item # 4100-2SS/2BSS – 3SS/3BSS – 35SS/35BSS

## Installation Instructions

Before you begin installation, please consult your local building code and/or pool code to ensure this product is suitable for your application. Routine maintenance and testing to ensure proper operation is required. Please leave these instructions with the consumer/end user and advise them about testing the latch routinely to ensure proper operation.

Quick Catch Item Number	Suitable for Gate Thickness	Space Required between the Gate and Post
4100-2SS or 4100-2BSS	1.75 – 2”	1.25”
4100-3SS or 4100-3BSS	2.75 – 3”	1.5”
4100-35SS or 4100-35BSS	3.25 – 3.5”	1.5”



1. Set the gate to open both ways by hanging between the gate posts. Allow for a 1.5” space between the gate and the latch post when using the 3” or 3.5” model or a 1.25” space if using the 2” model as shown here in Figure 1. (See table above for specific spacing) We strongly recommend the use of horizontally adjustable hinges when using the Quick Catch to allow for easy adjustment of the latch side spacing. The spacing requirement can vary only a small amount and still allow the Quick Catch to function, so adjustable hinges will make it easier to set up initially as well as easier to maintain in the future as the gate moves with the changes in weather, gate sagging, post heaving, etc.
2. If the gate is going to be ridden through on horseback, your gate and post will need to be made and set to a sufficient height to allow for the rider on their horse to reach the latch when it is mounted near the top of the gate as shown in Figure 2 with minimal leaning to avoid falling.
3. If the gate is going to be used by regular foot traffic or if wheelchair access is needed than the latch can be set lower on the gate and post to an appropriate height to allow for the type of traffic it will be used for. See example in Figure 3.
4. Once you have determined the best height to install the Quick Catch on the latch post you can then fasten it to the gate post using the 4 stainless steel lag bolts supplied. Remember to drill appropriately sized pilot holes for the lags to prevent the wood from splitting. See the final latch position on the latch post in Figure 4.
5. Test your overall installation to ensure proper and secure Quick Catch operation, make any necessary adjustments.



Snug Cottage Hardware Inc.  
 Marysville, MI USA & London, ON Canada  
[www.snugcottagehardware.com](http://www.snugcottagehardware.com)  
 Phone: (519)473-2794 - Fax: (519)474-3337