



FEATURES	RESIDENTIAL GATE OPERATORS					ELITE® SERIES DC COMMERCIAL GATE OPERATORS			HEAVY-DUTY DC COMMERCIAL GATE OPERATORS	
	Model Number	LA500PKGUL	LA400PKGUL	LA412PKGUL	RSL12UL	RSW12UL	CSW24UL	CSL24UL	HCTDCUL	HDSL24UL
<b>Description</b>	24VDC Residential/Light Commercial Linear Actuator	24VDC Residential Linear Actuator	12VDC Solar Residential Linear Actuator	12VDC Residential/Light Commercial Slide Gate Operator	12VDC Residential/Light Commercial Swing Gate Operator	24VDC High-Traffic Commercial Swing Gate Operator	24VDC High-Traffic Commercial Slide Gate Operator	Specialty Overhead Operator	24VDC Heavy Duty Commercial Slide Gate Operator	24VDC Heavy Duty Commercial Swing Gate Operator
<b>Max. Gate Weight</b>	1600 lbs.	850 lbs.	850 lbs.	800 lbs.	1000 lbs.	1600 lbs.	1500 lbs.	1000 lbs.	3000 lbs	2800 lbs./4500 lbs. w/optional arm (HDLGARM)
<b>Max. Gate Length</b>	18 ft.	16 ft.	16 ft.	25 ft.	16 ft.	18 ft.	50 ft.	16 ft. Door/Gate	75 ft.	22 ft. @ 2500 lbs. 14 ft. @ 4500 lbs.
<b>Gate Speed</b>	Opens 90° in 15-17 Seconds	Opens 90° in 15-17 Seconds	Opens 90° in 23-24 Seconds	10"/sec	Opens 90° in 12-15 Seconds	Opens 90° in 13-15 Seconds	1 ft/sec	8"-11"/sec Selectable	.5-1 ft/sec	Opens 90° in 13-36 Seconds
<b>Recommended Cycles</b>	300 cycles per day	100 cycles per day	100 cycles per day	120 cycles per day	250 cycles per day	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	High Cycle, High Temperature, Continuous duty on 8, 10 & 12 ft. rails. 600 cycles on 14 & 16 ft. rails.	Continuous Duty Up to 6M cycles	Continuous Duty Up to 6M cycles
<b>Battery Backup</b> Powers up when the power's down**	Yes	Yes	Solar	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Security+ 2.0® 3 Channel Receiver</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>MyQ®</b> Controls your gate from anywhere with your smartphone	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Monitored Safety Inputs</b> (Color Coded)	6 Inputs (Main and Expansion Board)	3 Inputs (Main Board)	3 Inputs (Main Board)	3 Inputs (Main Board)	3 Inputs (Main Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)
<b>DC Motor with Smooth Start/Stop</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes – Brushless Motor with Variable Speed	Yes – Brushless Motor with Variable Speed
<b>Diagnostic Code Display - 2 Digit LED</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Wireless Dual-Gate Operation</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Warranty Period</b>	2 Years	2 Years	2 Years	3 Years	3 Years	7 Years Residential 5 Years Commercial	7 Years Residential 5 Years Commercial	5 Years Commercial	7 Years Residential 5 Years Commercial	7 Years Residential 5 Years Commercial
<b>Power</b>	115V/230V Single Phase	115V Single Phase	Solar Powered only	115V Single Phase	115V Single Phase	115V/230V Single Phase	115V/230V Single Phase	115V/230V Single Phase	115V/230V Single Phase	115V/230V Single Phase

Note: LMRRUL/LMTBUL Heater option not recommended for solar applications. Heater option diminishes Standby time and cycles for Battery Backup.

For specifications and information on all our products, visit [LiftMaster.com/TOTALPAS](http://LiftMaster.com/TOTALPAS)  
**UL 325 LISTED DC GATE OPERATOR**  
**FEATURE CHART**

LMGTCTOOSBMC21 1/22

**LiftMaster®**



FEATURES	ELITE® SERIES AC COMMERCIAL/INDUSTRIAL GATE OPERATORS			
Model Number	CSW200UL	SL3000UL	SL585UL	SL595UL
<b>Description</b>	AC Commercial High-Traffic Swing Gate Operator	AC Commercial High-Traffic Slide Gate Operator	AC Industrial Slide Gate Operator	AC Heavy-Duty Industrial Slide Gate Operator
<b>Max. Gate Weight</b>	1/2 HP 1600 lbs. 1 HP 2000 lbs.	1/2 HP 1000 lbs. 1 HP 2000 lbs.	1/2 HP 1000 lbs. 1 HP 1600 lbs. 1 1/2 HP 1900 lbs.	1 HP 1700 lbs. 1 1/2 HP 2100 lbs. 2 HP 2500 lbs.
<b>Max. Gate Length</b>	1/2 HP 18 ft. 1 HP 22 ft.	1/2 HP 50 ft. 1 HP 50 ft.	1/2 HP 45 ft. 1 HP 70 ft. 1 1/2 HP 75 ft.	1 HP 70 ft. 1 1/2 HP 80 ft. 2 HP 90 ft.
<b>Gate Speed</b>	Opens 90° in 13–15 Seconds	1 ft/sec	11"/sec	1 ft/sec
<b>Recommended Cycles</b>	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	20 cycles per hour	25 cycles per hour
<b>Battery Backup</b> Powers up when the power's down**	-	-	-	-
<b>Security+ 2.0® 3 Channel Receiver</b>	Yes	Yes	Yes	Yes
<b>MyQ®</b> Controls your gate from anywhere with your smartphone	Yes	Yes	Yes	Yes
<b>Monitored Safety Inputs</b> (Color Coded)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board))
<b>DC Motor with Smooth Start/Stop</b>	-	-	-	-
<b>Diagnostic Code Display - 2 Digit LED</b>	Yes	Yes	Yes	Yes
<b>Wireless Dual-Gate Operation</b>	Yes	Yes	Yes	Yes
<b>Warranty Period</b>	7 Years Residential 5 Years Commercial	7 Years Residential 5 Years Commercial	2 Years	2 Years
<b>Power</b>	115V Single Phase	115V Single Phase	115/208/230VAC, Single Phase 208/230/460/VAC, 3 Phase - 575VAC, 3 Phase	115/208/230VAC, Single Phase 208/230/460/VAC, 3 Phase - 575VAC, 3 Phase

Note: LMRRUL/LMTBUL Heater option not recommended for solar applications. Heater option diminishes Standby time and cycles for Battery Backup.

For specifications and information on all our products, visit [LiftMaster.com/TOTALPAS](http://LiftMaster.com/TOTALPAS)  
**UL 325 LISTED AC GATE OPERATOR**  
**FEATURE CHART**

LMGTCTOOSBMC21 1/22

**LiftMaster®**