

ULTRALOOP® – ULT-II



VEHICLE LOOP DETECTOR WITH 7-PIN SCREW TERMINAL

The ULT-II is a compact, cost effective and reliable vehicle loop detector that is easy to set-up and install with a removable 7-pin screw terminal.

Sensitivity selection is simplified by the ULTRAMETER™ display that indicates the appropriate sensitivity setting to detect the vehicle positioned on the loop.

The 10 sensitivity settings allow for finer adjustment of the detection level, while the 4 frequency settings provide greater flexibility in preventing crosstalk in multi-loop applications.



ULT-II

scan here for more information



EMX Industries, Inc.

5660 Transportation Blvd, Garfield Heights, OH 44125

Phone: 800 426 9912

Fax: 216 518 9884

Sales Inquiries: salessupport@emxinc.com

Technical Support: technical@emxinc.com

www.emxinc.com



INDICATORS & CONTROLS

- DIP Switch 4 positions that control frequency, ASB (automatic sensitivity boost) and Pulse/Presence
- Sensitivity Rotary switch for fine-tune adjustment of loop detection height
- Output LED The Red LED indicates the detection output status
- ULTRAMETER™ Visual indicator of optimum loop sensitivity setting
- Power LED During operation, the Green LED permanently ON indicates a normal operating condition, blinking indicates a loop failure condition
- Frequency Count Switch Momentary push button to check operating frequency of the loop, indicated by the Red LED blinking at 10 KHz per blink



LD-7P



PR-XX

TECHNICAL DATA

Power Supply	12-24 VDC/AC
Current Draw	18 mA max.
Loop Inductance	20-2000μH (Q factor > 5)
Environmental Tracking	Automatic Compensation
Housing Material	ABS
Loop Compensation	Isolation transformer allows operation with poor quality loops
Loop Frequency	4 settings (low, med-low, med-hi, high)
Surge Protection	Loop circuitry protected by surge suppressors
ULTRAMETER™ Display	Indicates optimum sensitivity level, 0-9 diagnostic aid
Output	Relay 1A@24VDC Common, Normally Open, Normally Closed
Power/Loop Fault Indicator	Green LED
Detect/Frequency Count Indicator	Red LED
Frequency Count	To aid in detector set up and prevention of crosstalk
Pulse/Presence	Allows the relay output to send either a pulse output or have constant presence
Sensitivity	10 levels, 0-9
ASB (Automatic Sensitivity Boost)	Increases sensitivity after initial detection to prevent dropout due to high bed vehicles
Operating Temperature	-40o C-82o C (-40o F-180o F) 0-95% relative humidity
Dimensions (L x W x H)	3" (76 mm) x 0.9" (22 mm) x 2.75" (70 mm)
Weight	0.15 lbs. (68g)
Connection	7 position screw terminal

ORDERING INFORMATION

- ULT-II Ultra II Vehicle Loop Detector
- LD-7P 7 position screw terminal (included)
- PR-XX EMX Lite Preformed Loop with lightning protection (XX- specify size)

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of sale to our customer. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship. Rev 3 12/06/2022

