

CERTIFICATE OF COMPLIANCE

Certificate Number 20150728- BP7041
Report Reference BP7041-19971111
Issue Date 2015-July-28

Issued to: SECURITRON MAGNALOCK CORP
10027 S 51ST ST
PHOENIX AZ 85044-5219

**This is to certify that
representative samples of**

ACCESS CONTROL SYSTEM UNITS, SPECIAL LOCKING
ARRANGEMENTS , SIGNAL APPLIANCES,
MISCELLANEOUS CERTIFIED FOR CANADA
SEE ADDENDUM PAGE FOR MODELS

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL294, Standard For Access Control System Units,
ULC S533 Egress Door Securing and Releasing Devices

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20150728- BP7041
Report Reference BP7041-19971111
Issue Date 2015-July-28

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL1, CNL - Access Control System Accessories, Models XP-1 and XP-1F free-exit locking system consisting of the following subassemblies:

Security and General Signaling Subassembly:

USL2, CNL – Models BPS-12-3, -4.5, -6, -9, or -15, , -2, -3, -4, -6, or -10, BPS-3-CH, -4.5-CH, -6-CH, -9-CH, or -15-CH, BPS-24-2-CH, -3-CH, -4-CH, -6-CH, or -10-CH, BPSM-12-6, -9, or -15, BPSM-24-4, -6, or -10 Class 2 output power supplies; TSB-1, TSB, EL-TSB, TSB-B, TSB-BK, TSB-CL, EL-TSB-B, 3700, 3600, 3300, 3100, TSH-BK, EL-TSH-BK, or TSH-CL, EL-TSH-CL exit device; Series M32, M34, M38, M62, M68, and M82 locking devices, SAM Series locking devices, may be followed by suffixes C, S.; and LCP Lock Control Panel. Models may be prefixed with “FA”; Also consisting of the following recognized components: Dual Sense Bar, Model DSB will be followed by CL, BK, C, or B, may be followed by suffix 42, 48, I, A, IA, or M. Models may be prefix with EL or D.

USL2, CNL2 –Models BPS-12-1(-CH), BPS-24-1(-CH)

The TSH Series is covered under File BP7041, Vol. 1, Sec. 2, Report dated 06-16-97.

Security Subassembly and General Signaling:

USL2, CNL: Models PS-12-1M and PS-24-1M Power Supply Control Board Sub-assembly.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20150908-SA6635
Report Reference SA6635-20080724
Issue Date 2015-September-08

Issued to: SECURITRON MAGNALOCK CORP
10027 S 51ST ST, PHOENIX AZ 85044

This is to certify that representative samples of COMPONENT - SPECIAL LOCKING ARRANGEMENTS
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


Standard(s) for Safety: UL294, Access Control System Units,
ULC-S533-08 – Canadian Standard for Egress Door Securing
and Releasing Devices, NFPA 101 – Life Safety Code,

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus




CERTIFICATE OF COMPLIANCE

Certificate Number 20150908-SA6635
Report Reference SA6635-20080724
Issue Date 2015-September-08

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models:

USR, CNR - Recognized Component, Models: BPS-12/24-1, BPS-12, -1, -3, -4.5, -6, -9, -15, BPS-24, -1, -2, 3, -4, -6, -10, BPS-12, -1-CH, -3-CH, -4.5-CH, -6-CH, -9-CH, -15-CH, BPS-24, -1-CH, -2-CH, 3-CH, -4-CH, -6-CH, -10-CH, BPSM-12-6, -9, -15, BPSM-24-4, -6, and -10 Class 2 Output Power Supplies; XDT Logic Timers; LCP Lock Control Panel.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20150908-SA6635
Report Reference SA6635-19890807
Issue Date 2015-September-08

Issued to: SECURITRON MAGNALOCK CORP
10027 S 51ST ST, PHOENIX AZ 85044

This is to certify that representative samples of SPECIAL LOCKING ARRANGEMENTS
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 294 – Access Control System Units,
ULC-S533-08 – Canadian Standard for Egress Door
Securing and Releasing Devices,

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20150908-SA6635
Report Reference SA6635-19890807
Issue Date 2015-September-08

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.


Models:

USL, CNL: Models EXD-1 and EXD-1F Exit Delay Systems consisting of the following recognized components: BPS-12/24-1, BPS-12, -1, -3, -4.5, -6, -9, -15, BPS-24, -1, -2, 3, -4, -6, -10, BPS-12, -1-CH, -3-CH, -4.5-CH, -6-CH, -9-CH, -15-CH, BPS-24, -1-CH, -2-CH, 3-CH, -4-CH, -6-CH, -10-CH, BPSM-12-6, -9, -15, BPSM-24-4, -6, or -10 Class 2 Output Power Supplies, TSB-3, EL-TSB-3, TSB-3B, EL-TSB-3B, 3700, 3600, 3300, 3100 LMS-1, LML-1, LML-2, TSH-BK, EL-TSH-BK, TSH-CL, EL-TSH-CL, MXD-32 or MXD-62 Exit Devices; XDT Logic Timers; MK or MKN Mortise Keyswitch; Series M32, M62 with suffix C, DV, S, L, LS, F, G, B, D, or BD; M34 with suffix C, DV, S, L, LS, F, G, B, D, BD, or R; SAM with suffix C, B, D, BD, and/or S; M38, M68 with suffix C, DV, S, L, LS, F, G; M82 with one or more of the required suffixes C, DV, S, L, LS, F, G, B, or BD Locking Devices, and LCP Lock Control Panel. Models may be prefixed with "FA".

Also consisting of the following recognized components: SB-MXD, MXD-32 or MXD-62 Exit Devices.

Also consisting of the following recognized components: Dual Sense Bar, Model DSB will be followed by CL, BK, C, or B, may be followed by suffix 42, 48, I, A, IA, or M. Models may be prefix with EL or D.

CNL: Special Lock Arrangement Accessory, Exit Locks: Series M32 with suffix B, D, F, or any combination; M62 and M82 with suffix C, DV, S, L, LS, F, G, B, D, F, G or any combination, or BD; M34R with suffix C, DV, S, L, LS, F, G, B, D, BD, or R; SAM with suffix C, B, D, or BD, and/or S; M38, M68 with suffix C, DV, S, L, LS, D, or T.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

