

BULK STORAGE LOCKERS

4-Gauge Welded Wire Galvanized Steel

SPECIFICATIONS



4-gauge Stor-More Bulk Storage Locker Double Tier Starter model with Single Tier Add-on.



Full height hinged anti-pry locking bar



Locker bottom shelf option



Locker top and back option

All-galvanized steel
Bulk Storage Lockers provide sturdy, secure storage for tenants and businesses.

Panels 4-gauge galvanized welded wire mesh with 1½" x 3" openings.

Front Frame

14-gauge galvanized steel 1½" x 1½" x 90" angle.

Header Bar

14-gauge galvanized steel 3½" x 1" channel.

Rear Vertical Members

14-gauge galvanized steel 1½" x 1½" x 90" angle.

Doors 4-gauge galvanized welded wire mesh with 1½" x 3" openings. Full height hinged anti-pry locking bar and padlock hasp. Single Tier door has three 2" x 2" steel pin butt hinges, 86" Height; Double Tier and Triple Tier door has two 2" x 2" steel pin butt hinges for each door.

Double Units Include 22-gauge galvanized sheet metal shelf.

Finish Hot dipped galvanized.

Options Locker top constructed of 4-gauge galvanized welded wire mesh, 1½" x 3" openings.

Locker Back constructed of 1½" x 3" 8-gauge galvanized welded wire mesh; or 22-gauge galvanized sheet metal. Required for back to back units.

Modular design is easy to plan, install and relocate.

Available in single and double tier units, and can be combined. Begin with Starter unit, single or double, complete row with Add-On units.

Single Tier



Starter
1 Single tier door
2 End run panels



Add-On
1 Single tier door
1 Side panel

Double Tier



Starter
1 Double tier door
2 End run panels
1 Shelf



Add-On
1 Double tier door
1 Side panel
1 Shelf

Warranty 5-year.

www.hooverfence.com