

Round Post Adaptor Kit

Made in Australia

ded technologies

AUSTRALIA: 192 Harbord Rd, Brookvale NSW 2100 USA: 7731 Woodwind Drive, Huntington Beach, CA 92647

WARRANTY & LIMITATION OF LIABILITY: The products are warranted to be free of defects in materials and workmanship to the original purchaser for as long as he/she owns the product. If a defect appears, the original purchaser may return the item, freight prepaid, together with proof of purchase to the company or its approved international agents. The company or agent will, at its discretion, repair or replace the defective item or part without charge to the purchaser. THIS WARRANTY SHALL NOT APPLY WHEN the product has been tampered with, when repairs or attempted repairs have been made by unauthorised persons, where the item has been subjected to misuse, abuse, accident or damage in transit, or where the installer has not followed the instructions set out during installation or operations. IN NO EVEN SHALL THE COMPANY BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. No warranty is given other than that set out above. No other express or implied warranties (including statutory warranties) apply, other than warranties which may not be legally excluded.



The Round Post Adaptor Kit is for mounting 'Top Pull' or 'Vertical Pull' model latches to gates and fences with round posts. It comprises...

For the Latch:

- 2 x round-post mounting brackets for $2^3/8''$ diameter (A¹ & A²)
- 3 x round-post shims (for 2" dia.)
- 3 x round-post shims (for $2^{7}/8^{"}$ dia.)
- 3 x dress lugs

For the Striker Body:

- 1 x round-post mounting adaptor (A³)
- 2 x half-moon shims
- 1 x spacer packer (A⁴) is optional

With the appropriate combination of adaptors and shims, most common imperial and metric post diameters can be fitted. These include diameters ranging from $35 \text{mm} (1^{3}/\text{s}^{"})$ to $73 \text{mm} (2^{7}/\text{s}^{"})$.

The adaptor A³ is to be fitted in conjunction with L-shaped Striker Body mounting bracket. Cut off the side leg from this L bracket (see circle below).

The spacer A^4 is to be used only in applications where the gate and fence are not in alignment (typically a 1/2" or 12.7mm offset).

(Fasteners #3 and 5 supplied from Magna-Latch pack) (Use in conjunction with Magna Latch instructions) (Always cut off excess screw threads and file smooth)

