

# PhoneAire

*Wireless Telephone Entry*



The American Access Systems, Inc **PhoneAire** is a fully digital, wireless telephone entry system. The transmitter is constructed using a heavy gauge, powder coated enclosure and stainless steel faceplate that mounts directly to a pedestal or can be surface mounted. The **PhoneAire's** receiver is mounted in a standard rain-tight enclosure with a baked enamel finish and mounts directly to the side of the home or main building.

The **PhoneAire** allows the user to conveniently screen entrants from the home or office. When a guest presses the call button a unique ring cadence alerts someone that a guest is present at the gate. Communication is made from any phone on that line and access is granted by pressing the \*\* on the telephone's keypad. The gate can also be opened from inside the building without someone present at the gate.

This system features call forwarding, call waiting, "one-shot" code, sleep mode, full programming capability from the interior telephone, a manual override providing phone switching in the event of damage to the telephone entry unit and an optional pinhole camera (hardwired) for additional security. For pre-authorized entry, a fully programmable 500 code keypad is provided.

The **PhoneAire** telephone entry is a "No Phone Line" telephone entry system, allowing you to use your existing telephone line without creating an addition to the phone bill.



American Access Systems, Inc.

YOUR PARTNER IN ACCESS CONTROL

# PhoneAire



16-1050t



16-1050r



antenna ext (Optional)

## General Specifications

### 16-1050t Transmitter Unit

Input: 12 VAC or VDC AC (transformer included)  
Output: n/o or n/c contact 1-99 second  
Operating temperature: -15 to 175 Fahrenheit  
Dimensions: 7 3/8" H x 7 3/8" W x 5" D  
130mA continuous power usage  
Ship weight/16-1050r & 16-1050t: 9 lbs.  
Up to 3500 ft. communication range

### 16-1050r Receiver Unit

Input: 12 VAC or VDC AC (transformer included)  
Operating temperature: -15 to 175 Fahrenheit  
Dimensions: 7 3/8" H x 7 3/8" W x 5" D

## Relay Specs

	<u>DC Load</u>	<u>AC Load</u>
Contact Rating	2A @ 30V	.5A @ 125V
Max. switching voltage	125V	125V
Max. carrying current	2A	2A
Max. switching power	60W	62.5VA

## Features

- 500 access code capacity
- Personal Master code
- Call forwarding
- Call waiting
- Latch code
- Sleep mode
- Programmable "One-Shot" code
- Fully programmable from telephone
- 2 relays
- Adjustable volume:
  - microphone, speaker & phone tone
- Event Input
- Night Light
  - "60 second on" capability
- Unique ring cadence
- By-pass switch included
- Optional camera

## Manufactured by:

**American Access Systems, Inc**  
**7079 S Jordan Rd. Unit 6**  
**Centennial, CO 80112**  
**ph: (800) 541-5677**  
**fx: (303) 799-9756**  
**www.americanaccess.com**

## Distributed by: