

ACDx10xE5000 ACDx20/21xE5000

Access Controlled Doors

The ACDxE5000 EasyKit offers industry-proven life safety and security hardware for high-use, highabuse doors with a cost-effective access control solution.



(Shown on 10 Series Rim Exit Device - Available with 20/21 Series Surface Vertical Rod Devices)

Benefits -

- Cost-effective access control with panic hardware in one easyto-install kit
- · No key or cards to manage
- Audit trail provides additional security management
- Optional easy-to-use Excel-based software
- Pin code can be changed in seconds
- Easy-to-replace standard AA batteries
- Tough and durable design for years of trouble-free service in high-use, high-abuse environments
- Minimal door prep with no throughdoor wiring saves time and money

Features -

- E5000 features cast stainless steel internal drive parts
- Stainless steel deadlocking Pullman-type latch bolt on exit device
- Weatherproof trim requires no outside gasket
- Non-handed
- · Field sizeable panic device
- E5000 offers up to 100 access codes
- 1/8 turn dogging
- Heavy-duty angled end cap deflects damage away from panic device
- Battery pack included

For more information on 10/20/21 exit devices, see individual catalog pages For more information on E5000 visit www.kaba-ilco.com/access control

Mechanical Options -

- CD Cylinder Dogging
- HD Hex Dogging (Std.)
- LD Less Dogging

- 36 Fits 36" door width (Std.)
- 48 Fits 48" door width
- F 3 hour fire rated (both E5000 and panic device)
- H Hurricane Rated
- 99 surface strike (Std.)
- 98 semi mortise strike

Electrical Options -

- Exit Alarm (EA)
- Electric Dogging (ED)
- Electric Integration (EI)
- Electric Latch Retraction (ER)
- Delayed Egress Self Contained (EE)
- Delayed Egress with Latch Retraction (EExER)
- Delayed Egress Mag Lock (EM)
- Electric Switching (ES)
- Request to Exit (EX/EXV)
- Request to Exit Weatherized (EXxW)

Refer to Electrified Options section for more information



Accessories -

· SN1 - Sex Nut Fasteners

Technical Information -

- Door Types Wood, Hollow Metal, Fiberglass or Aluminum
- Door Thickness Fits standard 1-3/4" - 2-1/4" (for other door thicknesses, contact factory)
- SSK1 Torx Security Screw Kit
- Door Stile Fits minimum 5" wide stile with 99 strike (Std.)
- · Machine and Sheet Metal Screws (Std.)
- Rail Heavy Ribbed Aluminum Extrusion
- E5000 numeric pushbuttons vandal resistant, 12 button, metal keys
- E5000 construction is solid cast housing and solid cast zinc levers

Finishes (Kaba) -


- 626/26D Satin Chrome
- 606/04 Lifetime Satin Brass
- 695/55 Duranodic


• 605/03 Lifetime Bright Brass

Finishes (Advantex) -


- 605 / US3 Polished Brass
- · 606 / US4 Brushed Brass
- 611 / US9 Polished Bronze
- 612 / US10 Brushed Bronze
- 613 / US10B Oil Rubbed Bronze
- 629 / US32 Polished Stainless Steel
- 630 / US32D Brushed Stainless Steel

Riser Diagram -





Dimensions -



3 1/8" Extended

10 Series Dimensions Shown



Advantex -

UL Listed Panic Hardware

UL Listed Fire Exit Hardware

Listings and Approvals -



for 3 hours, maximum 4'x10' single doors and pairs of 4'x8' with F90KR keyed removable Mullion



Meets ADA requirements



UBC 97, Standard 7-2 and UL10C for positive pressure



ANSI/BHMA certified A156.3



Meets NFPA 80 & 101 for Life Safety



.. 2006 County, Florida NOA 04-0810.04 EXP. 04/07/10 Miami-Dade County, Florida 10 Series



California State Fire Marshall -4140-0127:105

Listings and Approvals -E5000



· 3 Hour UL & ULC fire rating for "A" labeled doors



Meets ADA requirements

ANSI/BHMA A156.2-2001

Detex Limited Warranty -

Advantex - 10 Year Mechanical / 3 Year Electrical Manufacturers **Limited Warranty**

E5000 - 3 year Manufacturers Warranty



Detex Corporation 302 Detex Drive New Braunfels, Texas 78130-3045 USA

PH. (830) 629-2900

(800) 729-3839 FAX (830) 620-6711

(800) 653-3839

http://www.detex.com

USA Sales: marketing@detex.com

International Sales: export@detex.com