



Cellular PVC Decking

General Specifications

Available Colors:

Sandstone	IPE
Clay	Walnut
Brookstone	Mahogany
Cobblestone	Ironwood

Materials:

Cellular PVC interior
SunShield® extreme weather-resistant exterior

Finish:

Low Gloss
Woodgrain Embossed

Product Specifications

Solid Deck Plank (5/4" x 6")*	12', 16', 20'	1.85 lbs./lin. ft.
HF Deck Plank (5/4" x 6")*	12', 16', 20'	1.80 lbs./lin. ft.
Fascia (3/4" x 10")	12'	2.80 lbs./lin. ft.
HF Biscuit	2.375"	N/A

*Nominal Size

Architect's Specifications 5/4" Solid Plank

PROPERTY	TEST METHOD	RESULT
Modulus of Rupture	ASTM 4761	>5,800psi
Modulus of Elasticity	ASTM 4761	>210,000psi
Coefficient of Linear Exp.	ASTM D696	3.2619E-05 (L/L) °f 1.8121E-05 (L/L) °C
Stair Tread	AC 174	Deflection <.125 at 12" Span
Creep Recovery	AC 174	94%
Hardness	ASTM D143	In-Progress
Accelerated Weathering	ASTM D2898-09	No Apparent Changes
California Ext. Wildfire Exposure	SFM 12-7A-4	Passed (Part A)
Flame Spread Index	ASTM E84	Class B
Slip Resistance (Dry)	ASTM 1679	In-Progress
Slip Resistance (Wet)	ASTM 1679	In-Progress
Screw Withdrawal	ASTM D1761	In-Progress
Impact Resistance	ASTM D4495	In-Progress

CCRR Tested in Compliance with ICC AC-174 Requirements
ATI Report #95796.01 CA SFM Intertek Report #3195900SAT-001

**Innovating solutions for
the environments of your life.™**

deceuninck

The name and logo of Deceuninck NV, of its affiliated companies and of the products and services manufactured by them, are trademarks and trade names protected by national and international laws. Sunshield is a registered trademark of Deceuninck North America.

© 2011 Deceuninck North America. All rights reserved. Part No. KOD-128 0211